



- Die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- With 3-phase universal track adaptor.
- 1-10V, DALI and switch dimming options available upon request.
- Alternatively wireless dim option available.
- Basic colours: white, black, silver, dark silver and special color options.
- Honeycomb filter, colour filter, antiglare screen and visor accesories available.
- Narrow, medium and wide beam angle options available with rotationally symmetric light distribution.

- Alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji giriřli.
- Akıllı soğutma tasarımı.
- 3-Fazlı üniversal ray adaptörü.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Alternatif olarak kablosuz dim seçeneđi mevcuttur.
- Standart renkler: beyaz, siyah, gri, koyu gri ve isteđe bađlı özel renk seçeneđi mevcuttur.
- Bal peteđi filtre, renk filtresi, kamařma önleyici ve ışık siperi aksesuar seçenekleri mevcuttur.
- Simetrik ışık çıkıřı sađlayan dar, orta ve geniş açđ reflektör seçenekleri mevcuttur.

VGL 12000

LED	COB LED	
Led Power / Led Gücü	13W	
System Power / Sistem Gücü	14W	
Lumen Output from Fixture / Armatür Çıkıř Lümeni CRI>80	2700K	1470
	3000K	1517
	3500K	1560
	4000K	1610
	5000K	1650
Lumen Output from Fixture / Armatür Çıkıř Lümeni CRI>90	2700K	1325
	3000K	1365
	3500K	1405
	4000K	1450
5000K	X	
Meat / Et COB	1800K	X
Food / Gıda COB	2400K	X
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu		✓
1-10V Dimming Option / 1-10V Dim Seçeneđi		✓
Dali Dimming Option / Dali Dim Seçeneđi		✓
Wireless Dim / Kablosuz Dim Seçeneđi		✓



Accessories / Aksesuarlar

