



VGL 12007

Order Code / Ürün Kodu	I02.LL.14128.45	I02.LL.14222.60	I02.LL.14227.75	I02.LL.14110.100	I02.LL.14210.120	I02.LL.14215.150
LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED
Led Power / Led Gücü	23W	46W	65W	119W	168W	232W
System Power / Sistem Gücü	25W	50W	70W	125W	175W	240W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	2540	5380	7605	14450	20410
	3000K	2615	5540	7830	14880	21020
	3500K	2670	5655	7990	15180	21450
	4000K	2720	5765	8150	15485	21870
	5000K	2805	5940	8395	15950	22530
Product Diameter / Ürün Çapı (A)	Ø450mm	Ø600mm	Ø750mm	Ø1000mm	Ø1200mm	Ø1500mm
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	✓	✓	✓	✓	✓
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓	✓	✓	✓

- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 120lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- 24V DC Electronic Led driver positioned outside luminaire.
- Steel suspension cord with up to 5mt length option.
- With lower profile height slim appearance.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzörü.
- 220-240V / 50-60Hz enerji girişi.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 120lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- 24V DC Led trafosu armatürün dışındadır.
- 5mt uzunluk seçeneğine kadar tercih edilebilir çelik sarkıtma tel.
- Kısa profil yüksekliği ile zarif görünüm.

Suspension Cord

Ray Sarkıtma Teli

