



VGL 12009

Order Code / Ürün Kodu	I02.LL.14145.45	I02.LL.14150.60	I02.LL.14155.75	I02.LL.14130.100	I02.LL.14135.120	I02.LL.14140.150
LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED	SMD LED
Led Power / Led Gücü	11.5W	23W	37W	57.5W	69W	105.5W
System Power / Sistem Gücü	12.5W	25W	40W	62.5W	75W	112.5W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	1295	2640	4305	6850	8370
	3000K	1330	2720	4436	7060	8620
	3500K	1360	2775	4525	7200	8795
	4000K	1390	2830	4615	7345	8970
	5000K	1430	2915	4750	7565	9240
Product Diameter / Ürün Çapı (A)	Ø450mm	Ø600mm	Ø750mm	Ø1000mm	Ø1200mm	Ø1500mm
Product Diameter / Ürün Çapı (B)	Ø300mm	Ø450mm	Ø600mm	Ø850mm	Ø1050mm	Ø1350mm
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	✓	✓	✓	✓	✓
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓	✓	✓	✓

- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 120lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- 24V DC Electronic Led driver positioned outside luminaire.
- Steel suspension cord with up to 5mt length option.
- With lower profile height slim appearance.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzör.
- 220-240V / 50-60Hz enerji girişi.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 120lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- 24V DC Led trafosu armatürün dışındadır.
- 5mt uzunluk seçeneğine kadar tercih edilebilir çelik sarkıtma tel.
- Kısa profil yüksekliği ile zarif görünüm.

Suspension Cord

Ray Sarkıtma Teli

