



- Corrosion resistant die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Can be used with high power Leds.
- Clever thermal design.
- 118lm/W system efficiency.
- Led colour temperatures optionally 3000K, 4000K and 5000K.
- Suitable for illumination up to 6-10 meter height.
- Dali control option available.
- Easy mounting possibility with mounting bracket.
- Reliable system with L80 B10 lifetime parameters.

- Korozyona dayanıklı alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji girişli.
- Power led uyumlu.
- Akıllı soğutma tasarımı.
- 118lm/W sistem verimliliği.
- 3000K, 4000K ve 5000K renk sıcaklığı seçenekleri mevcuttur.
- 6-10 metre yüksekliğe kadar aydınlatma sağlar.
- Dali kontrol uyumlu.
- Braket sistemi ile sahada kolay montaj olanağı sağlar.
- L80 B10 ömür parametrelerine sahip güvenli sistem.

## VGL 2000

POWER LED	Cree
Led Power / Led Gücü	185W
System Power / Sistem Gücü	190W
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K X
	3000K 21440
	4000K 22569
	5000K 23700
Number of Leds / Led Sayısı	48
Driving Current / Sürüş Akımı	700mA
Dali Dimming Option / Dali Dim Seçeneği	✓



High efficient optic design with different beam angle options increases the adaptability of the luminaire to different installation heights.

Yüksek verimli ve optik tasarımı ve farklı açı alternatifleri sayesinde farklı montaj yüksekliklerine kolayca uyum sağlar.

