




Light Grey

Textured Metallic
Dark Grey


Black



- Corrosion resistant die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Can be used Power Leds.
- Clever thermal design.
- Narrow, medium and wide beam angles available.
- Led colour temperatures optionally 2700K, 3000K, 4000K and 6000K.
- Alternatively blue, green, red and amber options available.
- Suitable for illumination up to 6-9 meter height.
- Internal silicon gaskets ensure IP protection.
- All external screws are stainless steel.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Up to 122lm/W efficiency
- High colour consistency: <3 SDCM

- Korozyona dayanıklı alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji girişi.
- Power led uyumlu.
- Akıllı soğutma tasarımı.
- Dar, orta ve geniş açı seçenekleri mevcuttur.
- 2700K, 3000K, 4000K ve 6000K renk sıcaklığı seçenekleri mevcuttur.
- Alternatif olarak mavi, yeşil, kırmızı ve amber renk seçeneği.
- 6-9 metre yüksekliğe kadar aydınlatma sağlar.
- Tüm dış vidalar paslanmazdır.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı.
- 122lm/W'a kadar ulaşan verim
- Yüksek renk uyumu: <3 SDCM

VGL 2006



Order Code / Sipariş Kodu	Led Type / Tipi	System Power / Sistem Gücü	mA	No. of Leds / Led Sayısı	Lumen T _c =60° Lümen	Kelvin / Color
O07.WL.00524.06	Cree XT-E	22W	700mA	9	2375 lm	2700K
O07.WL.00524.06	Cree XT-E	22W	700mA	9	2472 lm	3000K
O07.WL.00524.06	Cree XT-E	22W	700mA	9	2575 lm	4000K
O07.WL.00524.06	Cree XT-E	22W	700mA	9	2700 lm	6000K
O07.WL.00524.06	Cree XP-E	17.50W	700mA	9	2020 lm	Red / Kırmızı
O07.WL.00524.06	Cree XP-E	24W	700mA	9	2545 lm	Green / Yeşil
O07.WL.00524.06	Cree XP-E	23W	700mA	9	1155 lm	Blue / Mavi
O07.WL.00524.06	Cree XP-E	17.50W	700mA	9	1190 lm	Amber



Millimetric adjustment through bracket arm.

Özel braket sistemi ile milimetrik armatür açı ayarı yapılabilmektedir.