



- Corrosion resistant die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Can be used with high power Leds.
- Clever thermal design.
- 118lm/W system efficiency.
- Led colour temperatures optionally 3000K, 4000K and 5000K.
- Suitable for illumination up to 6-10 meter height.
- Dali control option available.
- Easy mounting possibility with mounting bracket.
- Reliable system with L80 B10 lifetime parameters.

- Korozyona dayanıklı alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji giriřli.
- Power led uyumlu.
- Akıllı soğutma tasarımı.
- 118lm/W sistem verimlilięi.
- 3000K, 4000K ve 5000K renk sıcaklıęı seçenekleri mevcuttur.
- 6-10 metre yüksekliğe kadar aydınlatma sağlanır.
- Dali kontrol uyumlu.
- Braket sistemi ile sahada kolay montaj olanaęı sağlar.
- L80 B10 ömür parametrelerine sahip güvenli sistem.

VGL 2009

POWER LED	Cree
Led Power / Led Gücü	135W
System Power / Sistem Gücü	140W
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K X 3000K 14540 4000K 14560 5000K 14700
Number of Leds / Led Sayısı	
Driving Current / Sürüş Akımı	700mA
Dali Dimming Option / Dali Dim Seçeneęi	✓

