



Light Grey

Textured Metallic
Dark Grey

Black



- Corrosion resistant die cast aluminium alloy.
- Thermal shock resistant safety glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, dark grey and light grey finish.
- Convenient to be used with COB led.
- Designed for single-side light output.
- Luminaire can be installed in any burning position.
- Narrow, medium and wide beam angles available.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- High colour consistency: <3 SDCM

- Korozyona dayanıklı alüminyum gövde.
- Paslanmaz çelik vida.
- Tamperli cam.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Tek taraftan ışık çıkışı olacak şekilde tasarlandı.
- Armatür aşağı veya yukarı bakacak şekilde istenildiği gibi monte edilebilir.
- Dar, orta ve geniş açı seçenekleri mevcuttur.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı gövde.
- Yüksek LED renk uyumu: <3 SDCM

VGL 4003

LED	COB LED	
Led Power / Led Gücü	2x26W	
System Power / Sistem Gücü	2x28W	
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	2x2900
	3000K	2x3021
	4000K	2x3140
	5000K	2x3290
Driving Current / Sürüş Akımı	700mA	

