


- Corrosion resistant aluminium alloy.
- Weatherproof and durable silicone rubber gasket.
- Stainless steel screws.
- Thermal shock resistant opal diffuser glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, light gray and antracite gray.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Fixing to ground: we recommend to concrete the root of the pole to improve stability.

- Korozyona dayanıklı alüminyum gövde.
- Su geçirmezliği sağlayan plastik conta.
- Paslanmaz çelik vida.
- Dış ortam koşullarına dayanıklı opal diffüzörlü.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı gövde.
- Yere montaj: armatürün alt kısmına daha güvenli montaj için düz beton yüzey oluşturulması tavsiye edilir.



Gray

Textured Metallic
Dark Gray

Black

VGL 7001

LED	SMD	
Led Power / Led Gücü	12W	
System Power / Sistem Gücü	15W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	1385
	3000K	1400
	4000K	1450
	5000K	1550

