


- Corrosion resistant aluminium alloy.
- Weatherproof and durable silicone rubber gasket.
- Stainless steel screws.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, light gray and antracite gray.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Fixing to ground: we recommend to concrete the root of the pole to improve stability.
- Lens optic with different beam angle options.

- Korozyona dayanıklı alüminyum gövde.
- Su geçirmezliği sağlayan plastik conta.
- Paslanmaz çelik vida.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımaya dayanıklı açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı gövde.
- Yere montaj: armatürün alt kısmına daha güvenli montaj için düz beton yüzey oluşturulması tavsiye edilir.
- Farklı açı seçeneklerine sahip lens optik.



Gray

Textured Metallic  
Dark Gray

Black

## VGL 7009

LED	Power LED
Led Power / Led Gücü	12W
System Power / Sistem Gücü	15W
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K 1575
	3000K 1690
	4000K 1790
CRI>80	5000K 1913



High efficient optic design with different beam angle options increases the adaptability of the luminaire to different project requirements.

Yüksek verimli ve optik tasarımı ve farklı açı alternatifleri sayesinde farklı uygulamalara kolayca adapte edilebilir.

