




C 180° C 0°

LED A A+ A++

CRI 70 CRI 80

CE GS IP 65



- Corrosion resistant aluminium alloy.
- Weatherproof and durable silicone rubber gasket.
- Stainless steel screws.
- Tempered glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in black, light gray and antracite gray.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Fixing to ground: we recommend to concrete the root of the pole to improve stability.
- Reflector optic with different beam angle options.

- Korozyona dayanıklı alüminyum gövde.
- Su geçirmezliği sağlayan plastik conta.
- Paslanmaz çelik vida.
- Tamperli cam.
- Su geçirmezliği sağlayan plastik conta.
- Ultraviyole ışımıya dayanıklı açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Çift katmanlı polyester toz boyası sayesinde korozyona ve tuza dayanıklı gövde.
- Yere montaj: armatürün alt kısmına daha güvenli montaj için düz beton yüzey oluşturulması tavsiye edilir.
- Farklı açı seçeneklerine sahip reflektör optik.



Gray



Textured Metallic Dark Gray



Black

### VGL 7011

LED	COB	
Led Power / Led Gücü	18W	
System Power / Sistem Gücü	20W	
Lumen Output from Fixture / Armatür Çıkış Lümeni	2700K	2275
	3000K	2400
	4000K	2500
CRI>80	5000K	2650

