



- Die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- Clear safety glass.
- Basic colours: white, black, silver, dark silver and special color options.
- Honeycomb filter and colour filter accessories available.
- Medium beam angle option available with rotationally symmetric light distribution.
- Emergency kit system can be integrated.
- Comfortable lighting with low UGR value.

- Alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji girişi.
- Akıllı soğutma tasarımı.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Tamperli cam.
- Standart renkler: beyaz, siyah, gri, koyu gri ve isteğe bağlı özel renk seçeneği mevcuttur.
- Bal peteği filtre ve renk filtresi aksesuar seçenekleri mevcuttur.
- Simetrik ışık çıkışı sağlayan orta açılı reflektör seçeneği mevcuttur.
- Acil aydınlatma kit sistemi uygulanabilir.
- Düşük UGR değeri sayesinde konforlu aydınlatma sağlar.

VGL 8012

LED	COB LED	
Led Power / Led Gücü	6W	
System Power / Sistem Gücü	7W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	605
	3000K	623
	3500K	640
	4000K	660
	5000K	681
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>90	2700K	550
	3000K	565
	3500K	585
	4000K	600
5000K	X	
Meat / Et COB	1800K	X
Food / Gıda COB	2400K	X
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu		✓
1-10V Dimming Option / 1-10V Dim Seçeneği		✓
Dali Dimming Option / Dali Dim Seçeneği		✓

