



- Die-cast aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- High efficient opal diffuser.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- IP44 rating possible with integration of extra silicon gasket upon request.
- Emergency kit system can be integrated.

- Alüminyum enjeksiyon gövde.
- 220-240V / 50-60Hz enerji girişli.
- Akıllı soğutma tasarımı.
- 1-10V, DALI ve faz dim seçenekleri bulunmaktadır.
- Yüksek verimli opal diffüzörlü.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- Ekstra silikon conta ilavesi ile koruma sınıfı IP44'e yükseltilebilir.
- Acil aydınlatma kit sistemi uygulanabilir.

VGL 8018

LED	SMD LED	
Led Power / Led Gücü	22W	
System Power / Sistem Gücü	24W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	2095
	3000K	2158
	3500K	2223
	4000K	2289
	5000K	2358
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>90	2700K	1900
	3000K	1960
	3500K	2022
	4000K	2080
	5000K	X
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	
Dali Dimming Option / Dali Dim Seçeneği	✓	

